



### 3D Vision & AI for Robots and More

# Mech-Mind Robotics Product Catalog

# We Help Integrators WIN with best-in-class AI + 3D vision tools and services.

Advanced Techs | Proven | Versatile | Fast and Easy | No Black-Box | Industry-Ready | Open | Best Services

# Empower System Integrators with Advanced AI + 3D Vision Tools

Mech-Mind is an industry-leading provider of industrial 3D cameras and AI software suites for robotic applications. With the comprehensive product portfolio, Mech-Mind empowers partners and system integrators to manage the most demanding robotic applications and brings automation to the next level.

### Mech-Eye Industrial 3D Cameras



- High accuracy
- Fast scanningResistance to ambient light
- IP65/IP67 protection and CE, FCC, VCCI, UKCA, KC, ISED, NRTL, and RoHS certified
- Multiple model options







### Mech-Vision Machine Vision Software

- · Code-free graphical user interface
- Extensive solution library
- Easy integration
- $\cdot\,$  Various vision tools integrated
- Integrates 1,000+ robot models



Quick recognition & precise positioning



### Mech-DLK Deep Learning Software

- Intuitive graphical user interface
- · Visualized model validation
- Simple labeling and fast training
- Easy integration using multi-language SDKs, including C, C++, C#, and Python
- Standalone AI software for quality control



Intuitive & efficient model training



### Mech-Viz Robot Programming Software

- Task-oriented graphical programming interface
- · One-click simulation
- · Powerful algorithms
- · Support for almost all major-brand robots



# **Mech-Eye Industrial 3D Cameras**

- · Detailed and accurate 3D point clouds
- Ambient light resistance
- Short capture time

- IP65 water and dust resistance
- Rugged aluminum alloy housing
- MTBF (Mean Time Between Failures): ≥ 40,000 hours

Scan the QR code to access

datasheets

Specification	LSR L	LSR S	PRO M	PRO S	UHP-140		
	*	5-2	se /	<u> </u>			
Recommended working distance <sup>[1]</sup>	1200–3000 mm	500-1500 mm	1000-2000 mm	500–1000 mm	300 ± 20 mm		
Near FOV	1200 × 1000 mm @ 1.2 m	480 × 360 mm @ 0.5 m	800 × 450 mm @ 1.0 m	370 × 240 mm @ 0.5 m	135 × 90 mm @ 0.28 m		
Far FOV	3000 × 2400 mm @ 3.0 m	1500 × 1200 mm @ 1.5 m	1500 × 890 mm @ 2.0 m	800 × 450 mm @ 1.0 m	150 × 100 mm @ 0.32 m		
Resolution	Depth map: 2048 × 1536	Depth map: 2048 × 1536		1920 × 1200	2048 × 1536		
	RGB: 4000 × 3000/ 2000 × 1500	RGB: 4000 × 3000/ 2000 × 1500	1920 × 1200				
Megapixels	/	/	2.3 MP	2.3 MP	3.0 MP		
Point repeatability Z $(\sigma)^{^{[2]}}$	0.5 mm @ 3.0 m	0.2 mm @ 1.5 m	0.2 mm @ 2.0 m	0.05 mm @ 1.0 m	2.6 µm @ 0.3 m		
					Region <sup>[3]</sup> : 0.09 µm @ 0.3 m		
VDI/VDE accuracy <sup>[4]</sup>	1.0 mm @ 3.0 m	1.0 mm @ 1.5 m	0.2 mm @ 2.0 m	0.1 mm @ 1.0 m	0.03 mm @ 0.3 m		
Typical capture time	0.5–0.9 s	0.5–0.9 s	0.3–0.6 s	0.3-0.6 s	0.6–0.9 s		
Baseline	380 mm	140 mm	270 mm	180 mm	80 mm		
Dimensions	459 × 77 × 86 mm	228 × 77 × 126 mm	353 × 57 × 100 mm	265 × 57 × 100 mm	260 × 65 × 142 mm		
Weight	2.9 kg	1.9 kg	1.9 kg	1.6 kg	1.9 kg		
Light source	Red laser (638 nm, Class 2)		Blue LED (459 nm, RG2)/White LED(RG2)		Blue LED (459 nm, RG2)		
Image sensor	Sony CMOS for high-end machine vision						
Operating temperature	-10–45°C		0-45°C				
Communication interface	Cigabit Ethernet						
Input	24V DC, 3.75 A						
Safety and EMC	CE/FCC/VCCI/KC/ISED/NRTL						
IP rating	IP65	IP67	IP65				
Cooling	Passive						



[1] Multiple focal distances are available in a camera model. For further details, please scan the QR code to access camera datasheets.

[2] One standard deviation of 100 Z-value measurements of the same point. The measurement target was a ceramic plate.

[3] One standard deviation of 100 measurements of the difference between the Z-value means of two same-sized regions. The measurement target was a ceramic plate. [4] According to VDI/VDE 2634 Part II.

# **Mech-Eye Industrial 3D Cameras**



- Detailed and accurate 3D point clouds
- Ambient light resistance
- Short capture time

- IP65 water and dust resistance
- Rugged aluminum alloy housing
- MTBF (Mean Time Between Failures): ≥ 40,000 hours

	DEEP	NANO ULTRA	NANO	PRO XS			
Specification	<u></u>			<u></u>			
Recommended working distance <sup>[1]</sup>	1200-3500 mm	250-800 mm	300-600 mm	300-600 mm			
Near FOV	1200 × 1000 mm @ 1.2 m	220 × 165 mm @ 0.25 m	220 × 150 mm @ 0.3 m	220 × 160 mm @ 0.3 m			
Far FOV	3500 × 2800 mm @ 3.5 m	770 × 550 mm @ 0.8 m	440 × 300 mm @ 0.6 m	430 × 320 mm @ 0.6 m			
Resolution	Depth map: 2048 × 1536	2/02 3000	1280 × 1024	1280 × 1024			
	RGB: 2000 × 1500	2400 × 1800					
Megapixels	/	4.3 MP	1.3 MP	1.3 MP			
Point repeatability Z $(\sigma)^{^{[2]}}$	1.0 mm @ 3.0 m	0.1 mm @ 0.6 m	0.1 mm @ 0.5 m	0.1 mm @ 0.5 m			
VDI/VDE accuracy <sup>[3]</sup>	3.0 mm @ 3.0 m	0.1 mm @ 0.6 m	0.1 mm @ 0.5 m	0.1 mm @ 0.5 m			
Typical capture time	0.5-0.9 s	0.5-0.9 s	0.6-1.1 s	0.7-1.1 s			
Baseline	300 mm	86 mm	68 mm	93 mm			
Dimensions	366 × 77 × 92 mm	125 × 46 × 76 mm	145 × 51 × 85 mm	160 × 52 × 87 mm			
Weight	2.4 kg	0.7 kg	0.7 kg	0.8 kg			
Light source	Red Laser (638 nm, Class 2)	Blue LED (440 nm, RG2)	Blue LED (459 nm, RG2)/White LED(RG2)	Blue LED (459 nm, RG2)			
Image sensor	Sony CMOS for high-end machine vision	High-performance CMOS for high- end machine vision	Sony CMOS for high-end machine vision				
Operating temperature	-10-45°C 0-45°C						
Communication interface	Gigabit Ethernet						
Input	24V DC	C, 3.75 A	24V DC, 1.5 A				
Safety and EMC	CE/FCC/VCCI/KC/ISED/NRTL						
IP rating	IP65						
Cooling	Passive						



Field of view (mm)

Multiple focal distances are available in a camera model. For further details, please scan the QR code to access camera datasheets.
One standard deviation of 100 Z-value measurements of the same point. The measurement target was a ceramic plate.
According to VDI/VDE 2634 Part II.

# Industrial 3D Camera Mech-Eye LSR L

### Long-Range Working Distance



MTBF (Mean Time Between Failures): ≥ 40,000 hours

#### High Accuracy | Large FOV | Ambient Light Resistance

The next-gen Mech-Eye LSR L can generate accurate, complete, and detailed 3D point cloud data of a wide variety of objects under severe ambient light interference (> 30,000 lx).



Track links



Gearbox housings



Brake discs Color rendered by height

Point clouds captured by Mech-Eye LSR L under challenging light conditions of > 30,000 lx @ 2.0 m



Crankshafts



Colored cartons



Colored sacks

Point clouds captured by Mech-Eye LSR L under challenging light conditions of > 30,000 lx @ 2.0 m

# Industrial 3D Camera Mech-Eye PRO



Medium-Range Working Distance

MTBF (Mean Time Between Failures): ≥ 40,000 hours

### High Accuracy | Fast Scanning Speed | Blue and White Light Options

Mech-Eye PRO delivers an extraordinary level of detail with super high accuracy. Capturing point clouds with accurate details takes as low as 0.3 s.



Dark and reflective objects Mech-Eye PRO S



Highly reflective metal parts Mech-Eye PRO S



Transparent groceries Mech-Eye PRO S



Reflective shafts Mech-Eye PRO S Color rendered by height



Colored goods Mech-Eye PRO M



Colored cartons Mech-Eye PRO M

Point clouds captured under typical indoor lighting conditions

# Industrial 3D Camera Mech-Eye NANO



Short-Range Working Distance

MTBF (Mean Time Between Failures): ≥ 40,000 hours

### Ultra-Small Size | High Accuracy | Ambient Light Resistance

Mech-Eye NANO (accuracy: 0.1 mm @ 0.5 m) can create 3D data of most complex parts with extraordinarily high accuracy. In space-critical applications, Mech-Eye NANO is easy to install and shows outstanding flexibility thanks to its ultra-small size (145 × 85 × 51mm).



Precision component



Thin objects (only 0.6 mm thick)



Various small workpieces

Point cloud examples captured by Mech-Eye NANO



Screws and nuts



Car charging port



Small parts

Point cloud examples captured by Mech-Eye NANO

# Industrial 3D Camera Mech-Eye NANO ULTRA





MTBF (Mean Time Between Failures): ≥ 40,000 hours

Ultra-High Precision | Palm Size | Ideal for Welding and Fine Assembly

Mech-Eye NANO ULTRA, featuring impressive ambient light resistance and anti-reflection capability, can capture clear, detailed point clouds of reflective weldments and metal parts even under strong light (60,000 lx)



Cylindrical metal part



H-beam



Sub-assembly component of the ship hull

Mech-Eye NANO ULTRA @ 0.6m, color rendered by height



Shiny steel plates with holes





Gas connectors

Bolts

Mech-Eye NANO ULTRA @ 0.6m

# Industrial 3D Camera Mech-Eye UHP-140

### Short-Range Working Distance



MTBF (Mean Time Between Failures): ≥ 40,000 hours

#### Micron-Level Accuracy | Robust Anti-Reflection Performance | Advanced Image Stitching Algorithms

Mech-Eye UHP-140 is designed to inspect or measure the subtlest features and defects (accuracy: 0.03 mm @ 0.3 m; standard: VDI/VDE 2634 part II of Germany).

Coupled with advanced image fusion and anti-reflection 3D reconstruction algorithms, Mech-Eye UHP-140 can effectively reduce blind spots and generate high-quality point clouds of reflective and complex-shaped parts.





Round positioning hole with chamfered edges

Threaded hole

Mech-Eye UHP-140 @ 0.3 m, color rendered by height



Reflective curved sheet metal part



Reflective enameled copper wire with a diameter of about 1.5  $\ensuremath{\mathsf{mm}}$ 

Mech-Eye UHP-140 @ 0.3 m, color rendered by height

### Mech-Vision Machine Vision Software

Mech-Vision is an industry-leading machine vision software. It is designed to quickly build vision applications, whether simple or complex. With Mech-Vision, users can manage a wide range of vision tasks, including identification, localization, inspection & measurement, etc.









## **Build your vision applications efficiently**

- Intuitive solution-oriented graphical user interface
- Drag-and-drop programming simplifies setup without writing a line of code
- Visualized configuration

## Manage complex vision applications with extensive tools

- Powerful algorithms: 2D/3D matching, 2D/3D deep learning, 2D/2.5D measurement, etc.
- Integrated machine vision tools: matching model, pick point editor, automatic calibration, caliper, etc.
- The **3D Workpiece Recognition** tool delivers recognition results in 1 sec, enabling easier and faster deployment of various loading and handling applications

## Develop vision applications easily and flexibly

- Robust Solution Library: get faster application deployment by adapting an existing project after simple modifications
- **Production Interface** for easy production status monitoring and data reporting
- Multiple languages: English, Japanese, Chinese, and Korean

## Mech-Viz Robot Programming Software

Mech-Viz is a software product for efficiently implementing robotic applications without writing a line of code. Mech-Viz enables robots to manage demanding automation tasks with excellent stability, extraordinary flexibility, and outstanding consistency.







#### ABB YASKAWA **KUKA** FANUC Kaw NACHI DENSO STÄUBLI EFORT UNIVERSAL BOBOTS **GREE** ROKAE ELITE ROBOTS 22 PETIAN M ESTUN 0 TURIN **R**AUBO UAR C HAN'S ROBOT JAKA SIASUN A DELTA

### **Intuitive Robot Programming**

- Intuitive graphical user interface
- Code-free programming environment
- One-click simulation of robot path

### Powerful Algorithms for Reliable Robotic Operation

- Motion planning and collision detection
- Multi-pick depalletizing algorithms
- Picking strategies: multiple pick points, rotational symmetry, etc.

### **Flexible and Easy Implementation**

- Support for almost all major-brand robots
- Streamlines configuration and redeployment with robot path reporting and tracking capabilities
- Multiple languages: English, Japanese, Chinese, and Korean

## Mech-DLK Deep Learning Software

Mech-DLK is a versatile deep learning software solving complex machine vision tasks. It enables users to rapidly train models and easily solve demanding vision applications, including overlapping object recognition and classification, complex defect detection, character reading, etc.







## Train models efficiently without writing a line of code

- Intuitive code-free user interface
- Visualized model validation
- Advanced data augmentation: train models with smaller image sets
- **Finetune** function: leverage pre-trained models to expedite training, rather than train a model from scratch

### Manage complex machine vision tasks with speed and accuracy

- Manages complex vision applications with powerful algorithms such as fast positioning, defect segmentation, and instance segmentation
- Smart Labeling Tool and Template Tool simplify the labeling process, saving time and effort



### Integrate your vision tasks into your production environment easily

- Multi-language SDKs: C, C++, C#, and Python
- Easy integration with Mech-Vision for quick deployment









Vision-Guided Case Depalletizing



Vision-Guided Sack Depalletizing



Vision-Guided EV Charging



Subframe Inline Measurement



Vision-Guided Case and Tote Depalletizing



Vision-Guided Machine Tending of Drive Gears



Vision-Guided Bin Picking of CV Joints



Vision-Guided Car Door Inner Panel Picking









Vision-Guided Machine Tending of Countershafts



Vision-Guided Heavy-Duty Truck Tire Assembly



Vision-Guided Tote Depalletizing



Vision-Guided Bolt Tightening



Vision-Guided De-racking of Stamping Parts



Vision-Guided Machine Tending of Battery Modules



Vision-Guided Depalletizing of Shrink-Wrapped Bottles



Inline Measurement of Bumper Beams



### **About Mech-Mind**

Mech-Mind is an industry-leading company focusing on industrial 3D sensors and software suites for intelligent robotics.

By combining 3D vision with AI technology, Mech-Mind brings automation to the next level and empowers partners and system integrators to manage the most challenging automation tasks, including bin picking, depalletizing & palletizing, picking & placing, and more.

#### **One of the Highest-Funded AI + Robotics Companies**

Founded in 2016, Mech-Mind has closed its Series C+ with total funding of > **USD 200 million**. Backed by Intel and other global top investors, Mech-Mind has been one of the highest-funded AI + robotics companies all over the world.

### Create Success Together with Partners and Integrators

Excellent usability, approved quality, high flexibility, comprehensive service, and competitive price, that's what we stand for and how we help our customers and partners to exceed in their business. Our mature solutions empower system integrators and partners to solve the most demanding applications and bring automation to the next level.

#### World-Class Team with Deep Technical Knowledge

Mech-Mind assembles highly qualified experts with rich technical knowledge in **3D sensing**, vision and robotics algorithms, robotics software, and intelligent robotic solutions.

#### 10,000+ Cameras Deployed

Mech-Mind partnered with industry-leading companies and has deployed applications in **50**+ regions. By delivering cutting-edge technology and reliable solutions, Mech-Mind has created visible ROI for global customers across diverse industries, including **automotive**, **metal and machining**, **logistics**, **home appliances**, **food and beverage**, **etc**.



### **3D VISION & AI FOR ROBOTS AND MORE**



### Get the most from Mech-Mind's 3D vision - get in touch with us!

Website: www.mech-mind.com E-mail (business): info@mech-mind.net E-mail (PR & marketing): marketing@mech-mind.net

### Learning guidance to deploy your vision application STEP BY STEP, please visit

Documentation: docs.mech-mind.net Online community: community.mech-mind.com